

# Tug Axis 1T/2T POWERED TUG



(Pictured with Auto-latching hitch—320mm height from ground)

A powerful machine, the Tug Axis is available in one or two tonne towing capacities.

Ideal for transporting medical carts around hospitals, moving heavy specialist equipment or moving heavy trolleys.

Using the tiller handle to tow the tug, the operator is in front of the load, increasing visibility and reducing the risk of collisions.

Powered towing can eliminate push/pull injuries caused by manually moving heavy trolleys or repetitive movements.



## Typical applications

Suitable for retail and light industrial towing including airports, factories, warehouses, apartment buildings or large facilities.

## Features

<b>Tow capacity</b>	<ul style="list-style-type: none"> <li>• Tug Axis 1T: 1000 kg</li> <li>• Tug Axis 2T: 2000 kg</li> </ul> (On flat ground, or with reduced towing capacity on ramps up to 8 degrees.)
<b>Max. speed</b>	Up to 5 km/hour
<b>Speed mode</b>	Three speed control with forward, reverse and emergency stop.
<b>Usability</b>	<ul style="list-style-type: none"> <li>• Turret with turret lock for easy reversing.</li> <li>• Easy to use with quiet, smooth operation.</li> </ul>
<b>Hitching</b>	Wide variety of hitches available for easy attachment to trolleys.
<b>Dimensions (L/W/H)</b>	1480/610/852 mm (handle down)
<b>Battery</b>	Two 12V-42Ah rechargeable batteries with 24V smart charger.

## Safety features

- Intuitive control with standard automatic safety brake, forward and reverse drive.
- Emergency stop and back-off safety buttons.

### ORDER CODES

Tug Axis 1T (no hitch)	TUGAXIS1TNH
Tug Axis 2T (no hitch)	TUGAXIS2TNH
Auto-latching hitch	EDHT1810-024
Pin hitch (16 mm)	EDHT1313
Pin hitch (19 mm)	EDHT1316
Clamp hitch (heavy duty)	EDHTCLAMP002*
Groove hitch	EDHTGROOVE001
Tow ball A-frame hitch	EDHT1810-023

\* EDHTCLAMP002: 1000 kg maximum capacity.