

Tug Axis 4T/5T POWERED TUG



[Pictured with an auto-latching hitch]

A powerful workhorse, the Tug Axis is available in four or five tonne towing capacities.

The Tug Axis is designed to improve safety and efficiency, whilst reducing the risk of accidents that can occur when manually moving very heavy loads.

Suitable for industrial towing or moving specialist equipment.

Ideal solution in helping to implement a 'no forklift zone' while protecting staff and products.



Typical applications

Suitable for large retail/facilities, heavy industrial towing, airports or factories.

Features

Tow capacity	<ul style="list-style-type: none"> • Tug Axis 4T: 4000 kg • Tug Axis 5T: 5000 kg (On flat ground, or with reduced towing capacity on ramps up to 8 degrees.)
Max. speed	Up to 4 km/hour
Speed mode	Three speed control with forward, reverse and emergency stop.
Usability	<ul style="list-style-type: none"> • Turret with turret lock for easy reversing. • Easy to use with quiet, smooth operation. • Zero emissions.
Hitching	Wide variety of hitches available for easy attachment to trolleys.
Dimensions (L/W/H)	<ul style="list-style-type: none"> • Tug Axis 4T: 1465/790/875 mm • Tug Axis 5T: 1740/900/905 mm
Battery	Two 12V-70Ah rechargeable batteries with 24V smart charger. <i>Optional upgrade: 100Ah batteries.</i>
Optional	Grey wheels

Safety features

- Emergency stop and back-off safety buttons.
- Intuitive control with standard automatic safety brake, forward and reverse drive.

ORDER CODES

Tug Axis 4T (no hitch)	TUGAXIS4TNH
Tug Axis 5T (no hitch)	TUGAXIS5TNH
Auto-latching hitch	EDHT1810-024
Pin hitch (19 mm)	EDHT1316
Pin hitch (29 mm) standard for 660/1100L bins	EDHT1810-052
Tow ball A-frame hitch	EDHT1810-023
Hydraulic arm lift kit	EDHYDARMLIFTKIT